

# JEWEL VAULTS

- **3" Body**
- **7" Door**
- **UL Listed**
- **TL30 Protection**
- **Combination Lock**



For use in the home or office, the Mutual TL30 Range of UL Safes, with its six-sided composite construction and 2-hour fire protection is the best choice.

## Construction

All around the world, the Mutual TL30 Range of UL Safes sets the standard in TL30 protection. The Safe's body consists of 18000PSI concrete, embodied with corundum aggregate and encased in a double layer of high tensile steel. The door is 7" in overall thickness and 3" of solid barrier material.



## Protection

Massive 2" chromed locking bolts, secured with a high-security U.L. listed Group II combination lock is standard on the TL-30 Safe. The lock is protected behind tempered glass, connected to a spring loaded relocker, which will activate in the event of a burglary. For ease of use, the safe incorporates an ingenious gear system which reduces friction and lets the safe owner use the tri-spoke handle with incredible ease.



**MUTUAL**

**SAFES**  
POWERED BY THE AGIC GROUP

info@mutual.co.za

| 012 803 6051

| www.mutual.co.za

## JEWEL VAULT SAFES - 3" Body & 7" Door

MODEL	EXTERNAL	INTERNAL	WEIGHT
JV 3020	36"H x 27"W x 31"D	30"H x 20"W x 22"D	1543 lbs
JV 4524	51"H x 30"W x 31"D	45"H x 24"W x 22"D	2204 lbs
JV 5524	61"H x 30"W x 31"D	55"H x 24"W x 22"D	2645 lbs
JV 6020	66"H x 26"W x 31"D	60"H x 20"W x 22"D	2425 lbs
JV 6034	66"H x 40"W x 31"D	60"H x 24"W x 22"D	3306 lbs
JV 6528	71"H x 34"W x 31"D	65"H x 28"W x 22"D	3086 lbs
JV 6836	74"H x 42"W x 36"D	68"H x 36"W x 27"D	4188 lbs



**MUTUAL**

**SAFES**  
POWERED BY THE AGIC GROUP

info@mutual.co.za

| 012 803 6051

| www.mutual.co.za